



## Raysun Polaris PD 50

### Pre-Diluted Radiator Coolant

Raysun Polaris PD 50 is a ready to use, prediluted (50/50) engine coolant based on mono ethylene glycol and advanced inorganic corrosion inhibitor without nitrites, amines and phosphates. The formulation is perfectly balanced in order to corrosion protection of all the metals and alloys used in the cooling systems specially aluminum, also protection against frost and excellent antifoaming characteristics. Raysun Polaris PD 50 is a 50/50 .volume mixture of Raysun Polaris with deionized water

#### Advantages

- Universal formula for automotive, heavy duty trucks and buses, light commercial vehicles and utility .vehicles
- .Protect the cooling system against freezing, corrosion and foaming
- .Compatible with cooling system filter
- .Compatible with rubber O-ring water pump seals, hoses or gasket material found in most cooling system

Note: This fluid is ready to use. DO NOT ADD WATER

#### Applications

- It can be used throughout the year in all cooling systems in gasoline and diesel engines
- For use in cooling systems of all types of liquid cooled automotive and internal combustion engines

#### Specifications

- ASTM D 3306



## Raysun Polaris PD 50

Values	ASTM Method	Test Parameters
8.8	D 1287	pH
6.5	D 1121	Reserve Alkalinity
108	D 1120	Boiling Point
-40	D 1177	Freezing Point

Note: "All of the results are typical and the results of each batch are presented in the COA sheet."