



Raysun ATF Dexron VI

Supreme performance Automatic Transmission Fluid

Raysun ATF Dexron VI is a supreme performance long life automatic transmission fluid specially developed for all 2006 and beyond General Motors vehicles equipped with Hydramatic automatic transmissions. This fluid is formulated with exceptional quality base fluids and advanced additive technology to provide outstanding oxidation resistance, friction durability, wear protection and shear stability. It is designed to provide twice the service life of a DEXRON® III (H) ATF and offers exceptional anti-shudder & smooth shift performance. It is fully back serviceable for DEXRON® III (H), DEXRON® III, DEXRON® II E and DE XRONR II D applications and offers enhanced performance for both new and older transmissions.

Advantages

- Outstanding thermo-oxidative stability, friction durability, wear protection and shear stability lead to Longer fluid life, Longer transmission life and Enhanced performance in both new and older transmissions
- Optimized frictional properties prevent clutch shudder and enable smooth gear shifting & extended clutch durability
- Exceptional viscosity profile, improved torque transfer and low viscosity of this oil help in improving fuel economy
- Enhanced foam control maintains responsive shifts and reduces wear on bearings, bushings and gears
- Excellent low temperature fluidity leads to easy pumping in the hydraulic circuits
- Special rust and corrosion inhibitors protect critical parts against rust and corrosion throughout the service life
- Excellent seal compatibility ensures longer seal life and reduces possibility of oil leakage

Applications

- Recommended for & meets the warranty requirements of all 2006 and beyond General Motors vehicles with six speed Hydra-Matic transmissions requiring DEXRON® VI quality fluids
- Being fully back serviceable, it is also recommended for automatic transmissions requiring DEXRON® III (H), DEXRON® III, DEXRON® II E and DEXRON® II D quality oils for enhanced performance

Specifications

- General Motors DEXRON VI



Raysun ATF Dexron VI

Typical Values	ASTM Method	Specification
6	D 445	Viscosity @ 100 °C, cSt.
164	D 2270	Viscosity Index
216	D 92	Flash Point, °C
-51	D 97	Pour Point, °C
11500	D 2983	Brookfield Viscosity, @-40 °C, cP

Note: "All of the results are typical and the results of each batch are presented in the COA sheet."