



Raysun Polarix 50%

Radiator Coolant

Raysun Polarix 50% is a ready-to-use, pre-diluted (50/50) engine coolant formulated with monoethylene glycol (MEG) and an advanced inorganic corrosion inhibitor system, free from nitrites and borates. It is premixed with demineralized water to provide optimum performance and protection. The formulation is carefully balanced to provide excellent corrosion protection for all metals and alloys commonly used in cooling systems, with particular protection for aluminum components. It also provides reliable frost protection and excellent anti-foaming properties, ensuring efficient and long-lasting cooling system performance.

Advantages

- Universal formula for automotive, heavy duty trucks and buses, light commercial vehicles and utility vehicles
- .Protect the cooling system against freezing, corrosion and foaming
- .Compatible with cooling system filter
- .Compatible with rubber O-ring water pump seals, hoses or gasket material found in most cooling system

Applications

- It can be used throughout the year in all cooling systems in gasoline and diesel engines
- For use in cooling systems of all types of liquid cooled automotive and internal combustion engines

Specifications

- ASTM D 3306



Raysun Polarix 50%

Values	ASTM Method	Test Parameters
8.8	D 1287	pH Aqu.
4.2	D 1121	Reserve Alkalinity
108	D 1120	Boiling Point (v/v), °C
-40	D 1177	Freezing Point (v/v), °C

".Note: "All of the results are typical and the results of each batch are presented in the COA sheet